

JENNY ENTRY LEVEL OIL FIRED HOT PRESSURE WASHERS

Standard Features

- Heavy Duty, Powder Coated, Roll Cage Frame with a 5 Year Limited Warranty
- Four Pneumatic Ball Bearing Wheels with Wheel Brake
- Industry Standard Gun Burner
- Two Quick Coupled 5 Gallon Fuel Tanks
- Direct Drive Triplex Ceramic Plunger Pump
- Off/Motor Burner Rotary Cam Switch enclosed in a Liquid Tight Junction Box
- 0, 15, 25, 40 Degree Color Coded Quick Connect Tips and one Brass Soap Tip
- Built-in Receiver for Optional Hose Reel
- Ground Fault Circuit Interrupter
- Stainless Steel Coil Casing Cover
- Nozzle Control
- Pressure Actuated Unloader
- High Pressure (Over Pressure) Relief Valve
- Thermal Pump Protection
- Low Pressure Chemical Injection
- 3/8" x 50' Quick Connect Hose
- High Capacity Inlet In-Line Water Strainer
- Handle Mounted Hose Rack
- Gun Holder
- One Year Limited Warranty

Optional Accessories

- Plastic Float Tank with High Pressure Soap Injection
- 13" or 16" Diameter Hose Reel
- Cleaning Wand Extensions
- High Speed Rotary Nozzle
- Wet Sand Blast Kit
- Variable Pressure Dual Lance Wand
- 25, 50 and 100 Foot Hose Extensions
- Additional 5 Gallon Fuel Tanks with Quick Couplers
- Backflow Preventor
- Rotary Brush



ELHW 1021
Shown with
optional reel



ELHW 1030
Shown with
optional reel



ELHW 2042



ELHW 2036
Shown with
optional reel



ELHW 1421

**Solving
Individual Cleaning
Problems Worldwide**

Model Number	ELHW 1021	ELHW 1030	ELHW 1421	ELHW 1530	ELHW2036	ELHW 2042
Discharge Value	2.1 GPM	3.0 GPM	2.1 GPM	3.0 GPM	3.6GPM	4.2 GPM
Operating Pressure	1000 PSI	1000 PSI	1350 PSI	1500 PSI	2000 PSI	2000 PSI
Operating Temperature	140° F Rise	140° F Rise	140° F Rise	140° F Rise	140° F Rise	140° Rise
Pump	Direct Drive Triplex Plunger	Direct Drive Triplex Plunger	Direct Drive Triplex Plunger	Direct Drive Triplex Plunger	Direct Drive Triplex Plunger	Direct Drive Triplex Plunger
Pump Motor	1.5 HP	2.0 HP	2.0 HP	3.0 HP	5.0 HP	5.0 HP
Voltage – Single Phase	115 Volt	115 Volt	115 Volt	230 Volt	230 Volt	230 Volt