








TECO20 *Special*

NEW TIRE CHANGER FOR MOTORCYCLE AND ATV WHEELS

-  TYRE CHANGERS
-  WHEEL BALANCERS
-  WHEEL ALIGNERS
-  LIFTING EQUIPMENT
-  MISCELLANEOUS EQUIPMENT

TECO20 – TECHNICAL FEATURES



In the picture TECO20 with optional accessories PR and SR (see on page 5)

TECHNICAL FEATURES – TECO20		
3-PHASE ELECTRIC MOTOR	0,5 HP	
1-PHASE ELECTRIC MOTOR	0,75 HP	
WORKING PRESSURE	8 – 10 BAR	116 – 145 PSI
BEAD BREAKER POWER	750 KG	1650 LB
MAX WHEEL DIAMETER	1000 MM	40"
TURNTABLE CLAMPING CAPACITY	5" – 23"	
MAX WHEEL WIDTH	220 MM	9"

GENERAL DESCRIPTION

- PROFESSIONAL SEMIAUTOMATIC TIRE CHANGER TO HANDLE **MOTORCYCLE**, **TURF**, **SCOOTER** AND **GO-KART** WHEELS
- THE SELF-CENTERING TURNTABLES LOCKS RIM FROM 5" A 23" THANKS TO 3 DIFFERENT CLAMPING POSITIONS WHICH CAN BE QUICKLY SELECTED WITHOUT USING ANY TOOLS
- HORIZONTAL BEAD BREAKING POSITION ENABLING THE USER TO CONTROL HIS ACTIVITY STILL REMAINING IN UPRIGHT POSITION
- FIXED BEAD BREAKER WHEEL SUPPORT HAVING MAXIMUM CAPACITY OF 220 MM (9")



In the picture TECO20 Special with bead breaker support in position (A), turntable with std clamping kit and optional accessories PR and SR (see on page 5)

GENERAL DESCRIPTION

- PROFESSIONAL SEMIAUTOMATIC TIRE CHANGER TO HANDLE MOTORCYCLE, TURF, SCOOTER, GO-KART AND ATVs WHEELS
- THE SELF-CENTERING TURNTABLES LOCKS RIMS FROM 5" TO 23" THANKS TO 3 DIFFERENT CLAMPING POSITIONS WHICH CAN BE QUICKLY SELECTED WITHOUT USING ANY TOOLS
- THE SELF-CENTERING TURNTABLES LOCKS RIMS FROM 6" TO 16" USING AN ATVs CLAMPING KIT (AVAILABLE ON DEMAND)
- HORIZONTAL BEAD BREAKING POSITION ENABLING THE USER TO CONTROL HIS ACTIVITY STILL REMAINING IN UPRIGHT POSITION
- INCREASED BEAD BREAKER CAPACITY TO WORK ON PARTICULARLY HIGH-PROFILE TIRES SUCH AS ATVs TIRES. THE BEAD BREAKER WHEEL SUPPORT IS EASILY MOVABLE IN 3 DIFFERENT POSITION HAVING MAXIMUM CAPACITY OF 370 MM (14,5")

TECO20 *Special* – TECHNICAL FEATURES



In the picture TECO20 Special with bead breaker support in position (B)

TECHNICAL FEATURES – TECO20 SPECIAL		
3-PHASE ELECTRIC MOTOR	0,5 HP	
1-PHASE ELECTRIC MOTOR	0,75 HP	
WORKING PRESSURE	8 – 10 BAR	116 – 145 PSI
BEAD BREAKER POWER	750 KG	1650 LB
MAX WHEEL DIAMETER	1000 MM	40"
➤ <i>TURNTABLE CLAMPING CAPACITY WITH</i>		
STANDARD MOTORCYCLE ADAPTERS	5" – 23"	
ATVs ADAPTERS (AVAILABLE ON DEMAND)	6" – 16"	
➤ <i>MAX WHEEL WIDTH</i>		
WITH BEAD BREAKER WHEEL SUPPORT IN POSITION (A)	190 MM	7,5"
WITH BEAD BREAKER WHEEL SUPPORT IN POSITION (B)	280 MM	11"
WITH BEAD BREAKER WHEEL SUPPORT IN POSITION (C)	370 MM	14,5"

TECO20 *Special* – ACCESSORIES




In the picture TECO20 Special with bead breaker support in position (C), turntable with ATVs clamping kit, cone for central hole ATVs wheels and optional accessories PR and SR

STANDARD ACCESSORIES


- BEAD **LEVER** AND GREASE **BRUSH**
- **PLASTIC PROTECTIONS** FOR BEAD BREAKER BLADE, HEAD TOOL AND LEVER
- **KIT GK** – ADAPTER KIT FOR GO-KART WHEELS

ACCESSORIES ON DEMAND

- **IG** – INFLATING GUN
- **KIT SR** – PATENTED SPECIAL WHEEL SUPPORT THAT ALWAYS KEEP THE WHEEL AT THE SAME DISTANCE FROM THE BLADE
- **KIT PR** – PATENTED ROLLER FOR FITTING CONTEMPORARILY THE 2 BEADS OF A TIRE HAVING DIAMETER SMALLER THAN 8” (I.E. SCOOTER)
- **TRS** – TOOL FOR SCOOTER WHEELS
- **UCA** – CLAMP KIT FOR CROSS MOTORCYCLE WHEELS



KIT SR –
Wheel support



KIT PR –
Mounting roller



TRS – Tool for
scooter wheels



ACCESSORIES ON DEMAND – ATV SPECIALS

- **CLAMPING KIT (1)** FOR ATV WHEELS WHICH LOCKS RIMS FROM 6" TO 16"
- SPECIAL **CONE (2)** TO SUPPORT SPECIAL CENTRAL HOLE ATVs WHEELS (TO BE USED AND COUPLED WITH THE KIT SR)

